

THE PROFESSIONAL DESKTOP PRINTER WITH LOW NOISE.

In addition to Kyocera's own controller language PRESCRIBE, this high performance printer comes with PCL6 and PostScript 3 emulation. The cost-effective ECOSYS technology ensures long-term gains.

- 18 pages per minute with 1,200 dpi quality
- 250-sheet closed paper cassette with paper gauge
- 3,000 pages starter toner
- Easy connection with USB and parallel interface
- Powerful controller with 32 MB RAM as standard
- PowerPC 405/266 MHz
- Long-life components

Optional network connectivity means people in a workgroup can easily share the printer.



A microfine toner for 6,000 pages minimises user intervention and guarantees large print runs.



FS-920

A4 MONOCHROME PRINTER

Ecosys® ECOSYS devices are designed to minimise both purchase costs and running expenses, such as maintenance, administration and consumables. The cartridge-free system requires only the toner to be replaced. The modular design concept allows you to add workflow-enhancing functions and a wide variety of paper handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

GENERAL

Technology: Kyocera ECOSYS, Laser

Engine speed: Max. 18 pages per minute A4

Resolution: 1,200 dpi quality (1,800 x 600)

Time to first page: 11 seconds

Warm-up time: 16 seconds from power off

Duty cycle: Max. 15,000 per month

Max. average 2,000 per month

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption: Printing: 315 W, Stand-by: 8 W,

Power-Saving (ECOPower): 4.8 W

Noise (ISO 7779): Printing: 49 dB(A), Stand-by: 28 dB(A),

Power-Saving (ECOPower): Immeasurably low

Dimensions (W x D x H): Main unit: 380 x 390 x 245 mm

Weight: Main unit: 9.2 kg (incl. Toner 9.5 kg)

Certifications: TÜV/GS, CE, PTS

This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: Universal paper cassette: 250 sheets, 60–105 g/m², A4, B5, A5, Letter, Legal, Custom (148 x 210 mm to 216 x 356 mm)

Manual feed (tray): 1 sheet, 60–163 g/m², A4, B5, A5, Letter, Legal, Custom (70 x 148 mm to 216 x 356 mm)

Output capacity: 100 sheets face down

System platform:

The FS-920 offers USB and parallel connectivity as standard as well as optional network connectivity and delivers problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device on the network; from single-user desktop printers to high end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high performance paper handling expertise.

PRESCRIBE IIe:

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

KM-NET for Clients/KM-NET Viewer:

The settings of all printers on the network can be checked visually and amended from any Windows® PC. KM-NET for Clients enables easy setup and monitoring of the printer status via parallel, USB or network connection. KM-NET Viewer is an advanced printer management software tool using the standardised protocol SNMP.

CONTROLLER

Processor: Power PC 405/266 MHz

Memory: Standard 32 MB + ECOmemory, max. 288 MB in 1 DIMM slot

Emulations: PCL 6/PCL 5e incl. PJL, KPDL 3 (PostScript 3 compatible), with automatic emulation sensing (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630

Controller language: PRESCRIBE IIe

FONTS: 80 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417

Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format

Print features: Manual duplex supported from printer driver

INTERFACES

Standard interface: High speed bi-directional parallel (IEEE 1284), USB 2.0 (Full speed)

Multiple Interface Connection (MIC): Allows simultaneous data transfer via up to two interfaces, with each interface having its own virtual printer.

CONSUMABLES

TK-110 Toner-kit: Microfine toner for 6,000 pages in accordance with ISO/IEC 19752

TK-110E Toner-kit: Microfine toner for 2,000 pages in accordance with ISO/IEC 19752

Capacity of starter toner is 3,000 pages in accordance with ISO/IEC 19752

WARRANTY

2-year warranty as standard. Kyocera guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.



KYOLife 3-year on-site warranty for extension for printer and options.

MODEL CONFIGURATIONS

FS-920N: Including external print server IB-100



Your Kyocera Business Partner: