

Panasonic

ideas for life



Colour Electronic Board

UB-2815C
UB-2315C



 **Panaboard**

“Direct & Colour” Office Solution

- Colour Scanning System
- SD Memory Card/USB Flash Memory Storage
- Direct Printer Output Capability
- USB PC Interface with Panasonic Document Management Software
- Automatic Date & Time Stamp

Colour Scanning Capability

Panaboard Anything you write on the whiteboard with colour markers can be scanned in colour, allowing you to capture and distribute an accurate colour representation of your meeting notes. The scanned data can be saved in colour, industry-standard PDF or JPEG file formats. A time stamp function allows you to insert the current date and time in the upper right corner of your saved images, facilitating easier organisation and filing.

SD Memory Card & USB Flash Memory

A built-in SD Memory Card slot and USB Flash Memory port allow you to store your data directly on a removable SD Memory Card or USB Flash Memory device and transfer it to a PC.



Dimensions (Including attached stand)

UB-2815C



UB-2315C



UB-2815C/UB-2315C Specifications

General	
Power Supply	AC 220-240 V, 50/60 Hz
Power Consumption	0.35 A/0.12 A (Operational/Standby)
External Dimensions* (H x W x D, with stand)	
UB-2815C:	1,858 mm x 2,014 mm x 1,207 mm [73.2" x 79.3" x 47.6"]
UB-2315C:	1,858 mm x 1,534 mm x 1,207 mm [73.2" x 60.4" x 47.6"]
Weight*	
UB-2815C:	37 kg (82 lbs)
UB-2315C:	30 kg (67 lbs)
Display	1.8" Colour LCD
Input Block	
Panel Dimensions (H x W)*	
UB-2815C:	869 mm x 1,781 mm [34.2" x 70.1"]
UB-2315C:	869 mm x 1,300 mm [34.2" x 51.1"]
Panel Surface	2 Steel Whiteboard (Front and Back side available by rotation)
Scanning Area (H x W)	
UB-2815C:	797 mm x 1,720 mm [31.3" x 67.7"]
UB-2315C:	797 mm x 1,240 mm [31.3" x 48.8"]
Scanning of Panels	2 flip-style surfaces (Front & Back)
Scanning System	Scanner Movement Scanning System using Contact Image Sensor
Scanning Time	
	Colour-Fine: 45 seconds
	Colour-Standard: 23 seconds
	B/W: 15 seconds
Memory Output Block	
Supported Memory Types	SD Memory Card, USB Flash Memory (Not included)
USB Flash Memory Interface	USB 2.0 (Full Speed, USB Master, A-Type Connector)
Support Format	
	SD Memory card: FAT16 format, Maximum capacity 2 GB
	USB Flash Memory: FAT16 format, Maximum capacity 2 GB
Store File Format	
	Colour Scanning: PDF or JPEG (JPEG Compression)
	B/W Scanning: PDF or TIFF (G4 Compression)
Printer Output Block	
Interface	USB 2.0 (Full Speed, USB Master, A-Type Connector)
Support Protocol	PCL 3 GUI (Most Compatible Color Ink-Jet Printers)
Print Resolution	300 dpi x 300 dpi
Continuous Printing	1 to 9 sheets
Print Size (H x W)	
UB-2815C	Standard size: 121.4 mm x 257.0 mm [4.7" x 10.1"] on A4 Size Paper
	Full size: 170.0 mm x 257.0 mm [6.6" x 10.1"] on A4 Size Paper
UB-2315C	Standard size: 168.4 mm x 257.0 mm [6.6" x 10.1"]
PC Interface	
Computer	IBM® PC/AT or compatible PC with a CD-ROM drive
CPU	Pentium II or higher processor
Interface	USB 2.0 or USB 1.1
Operating System	Windows® XP/2000
Memory	Windows® XP: 256MB or more, Windows® 2000: 128MB or more
Hard Disk	Min. 100MB free space (except saving space for data files)
Bundled Software	
USB & TWAIN Drivers	
Panasonic - DMS (Document Management System) Software	
Included Accessories & Consumables:	
Mobile Floor Stand	
Clock Battery (CR2032)	
Markers (1 Black, 1 Red and 1 Blue), Eraser & Magnets (2)	

www.panasonic.com.au

* Dimensions and weight are approximate.

- Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- IBM® is a trademark of International Business Machines Corporation in the United States, other countries, or both.
- Pentium is a trademark or registered trademark of Intel Corporation as its subsidiaries in the United States and other countries.
- All other brand or product names are the property of their respective holders.

Design and specification are subject to change without notice.

Panasonic

Panasonic
Customer
care
centre
132600