Panasonic ideas for life

electronic board

UB-5325 UB-5825 UB-7325

Panaboard[™]



Panaboard takes notes instead of you Improves your Presentations and meetings

Panaboard UB-5325, UB-5825, UB-7325

- Our range of Panaboards come with an integral printer for easy-operation.
- Plain paper printing with multiple copies.
- Panaboard can work as a PC printer.
- Panaboard can be controlled from PC.
- Panaboard keeps 100% audience attention and increases participation.
- Panaboard increases efficiency and reduces meeting time.
- Panaboard can be wall-mounted or used with floor-stand option.

Used for

Seminars


Meetings

Brain Storming

Scheduling

Training

PC Interface



Panaboard UB-5325, UB-5825 and UB-7325 come with utility software that consists of Document Manager and Document Viewer. The meeting contents on the Panaboard screen will

Panasonic Document Management System


become meeting minutes with some annotation by Document Viewer function. The Document Manager makes it easy to file and distribute the meeting minutes quite easily. Supported saving file format is BMP, TIFF, JPG, PNG and PDF.

> The scanned image is monochrome. The annotation function is used to make the coloured text.

Printer Driver

The Panaboard can also work as a PC printer. In a meeting, if you need to print out some documents, the Plug & Play of USB makes it easy to print out documents from the Panaboard.







1 Screen can also be used for the Projector. (UB-7325)

TWAIN Driver □ 1- 6/6

By just one click, you can scan the image on the Panaboard screen as image data to your computer and from your computer, you can control the

Panaboard function just like operating the Panaboard control panel.

| Specifications | | | | |
|---|-----------------------------------|--|---|--|
| General | Model number | UB-5325 | UB-5825 | UB-7325 |
| Power Supply | | AC 100 - 120 V, 50/60 Hz or AC 220 - 240 V, 50/60 Hz | | |
| Power Consumption (Operational) | | 1.40 A (AC 100 - 120 V) or 0.75 A (AC 220 - 240 V) | | |
| External Dimensions (Height X Width X Depth, without stand) | | 1,396 mm X 1,550 mm X 230 mm | 1,396 mm X 1,912 mm X 230 mm | 1,396 mm x 1,648 mm x 264 mm |
| Weight (without stand) | | 36.0 kg | 38.5 kg | 42.5 kg |
| Input Block | | | | |
| Panel Dimensions (Height X Width) | | 900 mm X 1,400 mm | 900 mm X 1,762 mm | 900 mm X 1,400 mm |
| Panel Surface | | 2 (endless type) | | 4 (endless type)*1 |
| Copying Area (Height X Width) | | 850 mm X 1.330 mm | 850 mm X 1.692 mm | 850 mm X 1.330 mm |
| Scanning System | | | Image sensors | |
| Output Block | | | | |
| Printing System | | Fusion thermal transfer type | | |
| Copy Paper | | Standard or recycled paper (60-90 g/m²) | | |
| Copy Paper size | | A4 or Letter | | |
| Copy Density | | 203 dpi (8 dots/mm) | | |
| Copy Color | Black | | | |
| Time Required for C | equired for Copying 15 sec./sheet | | | |
| Continuous Copies | | 1 to 9 | | |
| Contrast Adjustment | | Two levels : Normal/Dark | | |
| 2-screen Compress | ed Copying | | Yes | No |
| System Require | ements | | | |
| Computer | | IBM® PC/AT | or compatible machine with a CD-F | ROM drive |
| CPU | | Pentium® II or higher processor | | |
| Interface | | USB 1.1 or USB 2.0 (This electronic board functions with USB 1.1.) | | |
| Operating System | | Windows Vista™ (32 bits)*2, Windows® XP, Windows® 2000, Windows® 98, Windows® Me | | |
| Memory | | Windows® 98/Me: 64 MB or more, Windows® 2000: 128 MB or more, | | |
| | | Windows® XP: 256 MB or more, Windows Vista™: 512 MB or more | | |
| Hard Disk | | At least 240 MB free space (except saving space for image file) | | |
| Accessories | | | | |
| | | Operating instructions, Installation manual A4 or Letter Size Paper for test (20 sheets) | Power Cord Markers (black, Thermal Transfer Film (10 m) | , red and blue, one each) • Software CD-ROM • Eraser (one po |
| Optional Equipr | ment | | | |
| Wall-Mounting Kit | g Kit KX-B063 | | | |
| Stand | | KX-B061 | | |
| Separately Avai | ilable | | | |
| Replacement film | | UG-6001 (Set of 2 rolls [50 m]) | | |
| Markers | | KX-B031 (set of 10 black markers), KX-B032 (set of 10 red markers), KX-B033 (set of 10 blue markers) | | |
| | | KX-B042 (set of 6 erasers) | | |
| Erasers | | | NA-DU42 (SELUI O ELASEIS) | |

- Screen can also be used for the Projector.
- Please download the latest printer driver and application for

Windows Vista™ from the following web site: http://panasonic.co.jp/pcc/products/en/eboard/download/index.html



Note:

- Microsoft, Windows and Windows Vista are either registered trademarks or
- trademarks of Microsoft Corporation in the United States and other countries.

 Windows is Microsoft® Windows® operating system.

 IBM is a registered trademark of International Business Machines Corporation.
- Pentium is a registered trademark of intel Corporation in the U.S. and other countries.
 All trademarks referred to in this catalog are property of their respective companies.

http://panasonic.co.jp/pcc/en/







UB-7325 reen Standard size

(Stand option)